

U.S. Department of Commerce
National Oceanic & Atmospheric Administration

**QUALITY CONTROLLED LOCAL
CLIMATOLOGICAL DATA
(final)
HOURLY OBSERVATIONS TABLE
MAJORS AIRPORT (13926)
GREENVILLE, TX
(04/2014)**

National Climatic Data Center
Federal Building
151 Patton Avenue
Asheville, North Carolina 28801

Elevation: 535 ft. above sea level

Latitude: 33.067

Longitude: -96.065

Data Version: VER2

Date	Time (LST)	Station Type	Sky Conditions	Visibility (SM)	Weather Type	Dry Bulb Temp		Wet Bulb Temp		Dew Point Temp		Rel Humd %	Wind Speed (MPH)	Wind Dir	Wind Gusts (MPH)	Station Pressure (in. hg)	Press Tend	Net 3-hr Chg (mb)	Sea Level Pressure (in. hg)	Report Type	Precip. Total (in)	Alti-meter (in. hg)
						(F)	(C)	(F)	(C)	(F)	(C)											
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
25	0015	0	CLR	10.00		59	15.0	51	10.4	43	6.0	56	0	000		29.39			M	AA		29.96
25	0035	0	CLR	10.00		55	13.0	50	10.2	46	8.0	72	0	000		29.39			M	AA		29.96
25	0055	0	CLR	10.00		55	13.0	50	10.2	46	8.0	72	0	000		29.39			M	AA		29.96
25	0115	0	CLR	10.00		55	13.0	50	9.9	45	7.0	69	0	000		29.39			M	AA		29.96
25	0135	0	CLR	10.00		55	13.0	50	9.9	45	7.0	69	0	000		29.39			M	AA		29.96
25	0155	0	CLR	10.00		52	11.0	48	9.1	45	7.0	77	0	000		29.39			M	AA		29.96
25	0215	0	CLR	10.00		52	11.0	49	9.4	46	8.0	80	0	000		29.39			M	AA		29.96
25	0235	0	CLR	10.00		52	11.0	48	9.1	45	7.0	77	0	000		29.39			M	AA		29.97
25	0255	0	CLR	10.00		50	10.0	48	8.6	45	7.0	83	0	000		29.39			M	AA		29.97
25	0315	0	CLR	10.00		50	10.0	48	8.6	45	7.0	83	0	000		29.39			M	AA		29.97
25	0335	0	CLR	10.00		50	10.0	48	8.6	45	7.0	83	0	000		29.39			M	AA		29.97
25	0355	0	CLR	10.00		52	11.0	48	8.6	43	6.0	72	0	000		29.41			M	AA		29.98
25	0415	0	CLR	10.00		54	12.0	49	9.1	43	6.0	67	0	000		29.41			M	AA		29.98
25	0435	0	CLR	10.00		54	12.0	48	8.7	41	5.0	62	0	000		29.41			M	AA		29.99
25	0455	0	CLR	10.00		50	10.0	47	8.1	43	6.0	77	0	000		29.41			M	AA		29.99
25	0515	0	CLR	10.00		48	9.0	46	7.5	43	6.0	83	0	000		29.42			M	AA		30.00
25	0535	0	CLR	10.00		48	9.0	46	7.5	43	6.0	83	0	000		29.44			M	AA		30.01
25	0555	0	CLR	10.00		48	9.0	46	7.5	43	6.0	83	0	000		29.44			M	AA		30.02
25	0615	0	CLR	10.00		48	9.0	46	7.5	43	6.0	83	0	000		29.45			M	AA		30.03
25	0635	0	CLR	10.00		52	11.0	49	9.1	45	7.0	77	0	000		29.45			M	AA		30.03
25	0655	0	CLR	10.00		55	13.0	50	9.9	45	7.0	69	0	000		29.47			M	AA		30.04
25	0715	0	CLR	10.00		57	14.0	51	10.4	45	7.0	64	3	100		29.47			M	AA		30.04
25	0735	0	CLR	10.00		59	15.0	52	10.9	45	7.0	60	0	000		29.47			M	AA		30.05
25	0755	0	CLR	10.00		63	17.0	54	11.9	45	7.0	52	3	120		29.48			M	AA		30.06
25	0815	0	CLR	10.00		64	18.0	53	11.7	43	6.0	47	5	120		29.49			M	AA		30.07
25	0835	0	CLR	10.00		68	20.0	52	11.3	37	3.0	32	10	100		29.49			M	AA		30.07
25	0855	0	CLR	10.00		68	20.0	52	11.1	36	2.0	31	8	110		29.49			M	AA		30.07
25	0915	0	CLR	10.00		70	21.0	53	11.6	36	2.0	29	9	100		29.49			M	AA		30.07
25	0935	0	CLR	10.00		72	22.0	54	12.1	36	2.0	27	9	110		29.50			M	AA		30.08
25	0955	0	CLR	10.00		72	22.0	53	11.7	34	1.0	25	10	110		29.50			M	AA		30.08
25	1015	0	CLR	10.00		73	23.0	53	11.6	32	0.0	22	9	100		29.49			M	AA		30.07
25	1035	0	CLR	10.00		73	23.0	53	11.6	32	0.0	22	10	130		29.49			M	AA		30.07
25	1055	0	CLR	10.00		75	24.0	53	11.7	30	-1.0	19	9	150		29.49			M	AA		30.07
25	1115	0	CLR	10.00		75	24.0	54	12.1	32	0.0	21	8	120		29.48			M	AA		30.06
25	1135	0	CLR	10.00		75	24.0	54	12.1	32	0.0	21	7	120		29.48			M	AA		30.06
25	1155	0	CLR	10.00		77	25.0	55	12.5	32	0.0	19	8	160		29.47			M	AA		30.04
25	1215	0	CLR	10.00		77	25.0	55	12.5	32	0.0	19	8	160		29.47			M	AA		30.04
25	1235	0	CLR	10.00		77	25.0	54	12.2	30	-1.0	18	3	120		29.45			M	AA		30.03
25	1255	0	CLR	10.00		77	25.0	55	12.5	32	0.0	19	6	110		29.44			M	AA		30.02
25	1315	0	CLR	10.00		79	26.0	55	13.0	32	0.0	18	7	150		29.44			M	AA		30.01
25	1335	0	CLR	10.00		79	26.0	55	13.0	32	0.0	18	8	170		29.42			M	AA		30.00
25	1355	0	CLR	10.00		79	26.0	56	13.3	34	1.0	20	9	160		29.41			M	AA		29.99
25	1415	0	CLR	10.00		79	26.0	55	13.0	32	0.0	18	7	160		29.41			M	AA		29.99
25	1435	0	CLR	10.00		79	26.0	55	13.0	32	0.0	18	8	180		29.41			M	AA		29.98
25	1455	0	CLR	10.00		79	26.0	55	13.0	32	0.0	18	5	180		29.39			M	AA		29.97
25	1515	0	CLR	10.00		79	26.0	56	13.3	34	1.0	20	9	150		29.39			M	AA		29.97
25	1535	0	CLR	7.00		79	26.0	56	13.3	34	1.0	20	8	170		29.39			M	AA		29.96
25	1555	0	CLR	10.00		79	26.0	56	13.3	34	1.0	20	6	150		29.38			M	AA		29.95
25	1615	0	CLR	10.00		79	26.0	55	12.9	32	0.0	18	7	150		29.36			M	AA		29.94
25	1635	0	CLR	10.00		79	26.0	56	13.3	34	1.0	20	7	170		29.36			M	AA		29.93
25	1655	0	CLR	10.00		79	26.0	56	13.3	34	1.0	20	7	160		29.36			M	AA		29.93
25	1715	0	CLR	10.00		79	26.0	56	13.3	34	1.0	20	7	160		29.36			M	AA		29.93
25	1735	0	CLR	10.00		79	26.0	57	13.6	36	2.0	21	6	140		29.35			M	AA		29.92
25	1755	0	CLR	10.00		77	25.0	56	13.4	37	3.0	24	6	130		29.34			M	AA		29.91
25	1815	0	CLR	10.00		73	23.0	57	13.8	43	6.0	34	3	120		29.34			M	AA		29.91
25	1835	0	CLR	10.00		70	21.0	56	13.5	45	7.0	41	3	120		29.34			M	AA		29.91
25	1855	0	CLR	10.00		68	20.0	56	13.3	46	8.0	45	3	110		29.34			M	AA		29.91
25	1915	0	CLR	10.00		66	19.0	53	11.7	41	5.0	40	0	000		29.33			M	AA		29.90
25	1935	0	CLR	10.00		63	17.0	54	11.9	45	7.0	52	5	110		29.33			M	AA		29.90
25	1955	0	CLR	10.00		63	17.0	54	11.9	45	7.0	52	3	110		29.34			M	AA		29.91
25	2015	0	CLR	10.00		61	16.0	54	12.2	48	9.0	63	0	000		29.35			M	AA		29.92
25	2035	0	CLR	10.00		61	16.0	54	12.2	48	9.0	63	0	000		29.35			M	AA		29.92
25	2055	0	CLR	10.00		59	15.0	52	11.2	46	8.0	62	3	120		29.35			M	AA		29.92
25	2115	0	CLR	10.00		61	16.0	53	11.4	45	7.0											