

FAR PART 125
OPERATING MANUAL
FOR
FERRETERIA E IMPLEMENTOS
SAN FRANCISCO
VOLUME 2 TITLE MAINTENANCE

UNIVERSAL REPORT FORM

(Use for Making Reports or Listing Non-Routine Maintenance Items)

Name _____ Subject _____ Date _____ Airplane No. N24DR

Avionics Services International. CRS S78R151N

Date: Jun 13, 2019 Aircraft /Model/S/N N24DR

FAR 91.411 I Certify that the Altimeter and Reporting equipment system has been tested, Inspected, and found to comply with appendices E and F of part 43 of this chapter. The static and reporting system was tested

FAR 91.413 I Certify that the ATC transponder system has been tested, Inspected, and found to comply with paragraph (c) appendix E, of part 43 of this chapter. The integrated system was tested.

FAR 91.411 ALT. P/N 5934PA-1 S/N AN WAS TEST TO 25,000 FT. AND PASS.

FAR 91.411 ALT. P/N 8140B-20 S/N 3794 WAS TEST TO 25,000 FT AND PASS.

FAR 91.411 ENCODER D120-P2-T S/N 29922 WAS TEST TO 25,000 FT AND PASS.

FAR 91.411 ENCODER AK-350 S/N 73005 WAS TEST TO 25,000 FT AND PASS.

FAR 91.413 TDR KT76A S/N 125906 WAS TEST AND PASS.

FAR 91.413 TDR AT-150 S/N 28507 WAS TEST AND PASS.

LEAK RATE 12 FT. A/C TOTAL TIME 47,736.4

Workorder No. 6233

Date: Jun 13, 2019

Signature

ASI -13,14

FORM-7

CARD NO. CV-203
PAGE 1 of 1CHECK # _____
CV-440 Date _____ N # 240R
FIRE EXTINGUISHER - 12 MONTH RE-WEIGH

MECHANIC

1. Cockpit Fire Extinguisher
 - A. Remove from bracket and inspect for damage, rust & quantity via visual sight gauge.
P/N: 5TCM 8 S/N: CC 547 055
 - B. Weigh unit and insure it falls within 2% of placarded weight.
Note weight: 8 lbs
Placarded weight: 7 lbs 15 oz.
 - C. Install yellow tag noting date of re-weigh & next weigh check due. Install unit in bracket.
Insure unit fits properly & stays secured.
2. Forward Cabin Fire Extinguisher
 - A. Remove from bracket and inspect for damage, rust & quantity via visual sight gauge.
P/N: 5TCM 8 S/N: CC 596 095
 - B. Weigh unit and insure it falls within 2% of placarded weight.
Note weight: 15 lbs
Placarded weight: 15 lbs
 - C. Install yellow tag noting date of re-weigh & next weigh check due. Install unit in bracket.
Insure unit fits properly & stays secured.
3. Aft Cabin Fire Extinguisher
 - A. Remove from bracket and inspect for damage, rust & quantity via visual sight gauge.
P/N: B 933 708 S/N: 139337 08
 - B. Weigh unit and insure it falls within 2% of placarded weight.
Note weight: 2.5 lbs
Placarded weight: 2.5 lbs
 - C. Install yellow tag noting date of re-weigh & next weigh check due. Install unit in bracket.
Insure unit fits properly & stays secured.

Mechanics Signature: _____

A&P No.: _____

Date (completed): _____

Next Re-weigh Due: 6/1/2019

Revision: Original