

LOC I-BMG <u>108.3</u>	APP CRS 354°	Rwy Idg TDZE Apt Elev	6500 844 846
----------------------------------	------------------------	-----------------------------	---

ILS or LOC/DME RWY 35
MONROE COUNTY (BMG)


▼ Circling to Rwy 6/24 NA at night. When local altimeter setting not received, use Terre Haute Rgnl altimeter setting; increase S-ILS 35 DA to 1165 and all MDA 140 feet and increase S-ILS 35 all Cats visibility $\frac{1}{4}$ SM, S-LOC 35 Cat C and D and Circling Cat C and D visibility $\frac{1}{2}$ SM. For inoperative MALSR when using Terre Haute Rgnl altimeter setting; increase S-ILS 35 all Cats visibility to $1\frac{1}{4}$ miles. DME from OOM VORTAC. Simultaneous reception of I-BMG and OOM DME required.

MALSI

A5

MISSED APPROACH:
Climb to 2000 then
climbing left turn to
2500 direct OOM
VORTAC and hold.

ASOS 134.525	HULMAN APP CON 128.025 339.8	BLOOMINGTON TOWER ★ 120.775 (CTAF) 0	GND CON 121.9	UNICOM 122.95
-----------------	---------------------------------	---	------------------	------------------



DME REQUIRED

ELEV 846	TDZE 844
HIRL Rwy 17-35 (1)	MIRL Rwy 6-24 (1)

FAF to MAP 5 NM					
Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40