

SECTION 3: SPECIFICATIONS AND CAPABILITIES**A GENERAL**

1. Weight

(a)	Without ballast	20,000 lb (9,070 kg)
(b)	With ballast (Opt.)	22,000 lb (9,979 kg)
(c)	With ballast (Opt.)	30,000 lb (13,636 kg)
(d)	With ballast (Opt.)	35,000 lb (15,910 kg)
(e)	Fully ballasted (Opt.)	40,000 lb (18,140 kg)

2. Drawbar Pull (At 0.8 traction coefficient)

(a)	At GVW 20,000 lb (9,070 kg)	16,000 lb (7,272 kg)
(b)	At GVW 30,000 lb (13,636 kg)	24,000 lb (10,910 kg)
(c)	At GVW 35,000 lb (15,910 kg)	28,000 lb (12,727 kg)
(d)	At GVW 40,000 lb (18,140 kg)	28,000 lb (13,608 kg)

3. Speed

(a)	Forward 1st	2.5 mph (4.0 km/h)
(b)	Forward 2nd	5.75 mph (9.3 km/h)
(c)	Forward 3rd	13.25 mph (21.3 km/h)
(d)	Forward 4th	15 mph (24.1 km/h)
(d)	Reverse 1	2.5 mph (4.0 km/h)
(e)	Reverse 2	6.0 mph (9.7 km/h)
(f)	Reverse 3	13.0 mph (20.1 km/h)

4. Length

(a)	Without hitches	181.75 in (4,616.5 mm)
(b)	With standard hitches	207 in (5,258 mm)

5. Width

Width	89 in (2,260 mm)
-------------	------------------