

Summary Listing		Complete Listing		Interval Listing		Data Analyses		Severe Weather	
Level	Height (ft-MSL)	Pres (mb)	T (C)	Td (C)	RH (%)	DD / FF (deg / kts)	CAT (FAA)	LLWS	Icing - (AFGWC)
1	541	992	18.8	16.0	84	195 / 7			
2	1698	952	16.0	14.4	90		XTR	LIGHT	
3	2000	942				220 / 33	LGT		
4	2501	925	15.0	13.9	93	225 / 37	MDT	LIGHT	
5	3000	909				235 / 44			
6	3109	905	14.4	12.2	87				
7	3480	893	14.6	12.0	84				
8	3668	887	15.2	9.2	67				
9	3889	880	16.6	4.6	45		LGT		
10	4080	874	18.2	-19.8	6	235 / 40			
11	4209	870	19.0	-30.0	2				
12	4731	854	20.2	-22.8	4		SVR		
13	4863	850	20.0	-25.0	3	225 / 31	LGT		
14	4929	848	19.8	-26.2	3	220 / 27			
15	5535	830	21.8	-16.2	7		SVR		
16	6000	816				245 / 21			
17	6400	805	20.4	-15.6	8				
18	7000	788				250 / 22			
19	8000	760				250 / 23			
20	9000	733				250 / 23			
21	10002	707	10.2	-13.8	17	250 / 22			
22	10273	700	9.4	-14.6	17	245 / 22	LGT		

Summary Listing		Complete Listing		Interval Listing		Data Analyses		Severe Weather	
Level	Height (ft-MSL)	Pres (mb)	T (C)	Td (C)	RH (%)	DD / FF (deg / kts)	CAT (FAA)	LLWS	Icing - (AFGWC)
1	1007	977	11.8	5.8	67	120 / 6			
2	1092	974	13.4	4.4	54				
3	1292	967	16.0	5.0	48				
4	1524	959	18.0	7.0	49		XTR	LIGHT	
5	2000	943				235 / 21	SVR	LIGHT	
6	2540	925	19.0	8.0	49	260 / 29			
7	2601	923	19.0	8.0	49				
8	3000	910				260 / 31			
9	3405	897	17.6	7.6	52		LGT		
10	4000	878				255 / 28			
11	4646	858	15.2	1.2	39		LGT		
12	4906	850	14.6	1.6	41	250 / 26	MDT		
13	6100	814	11.6	2.6	54	235 / 22			
14	6337	807	11.4	-0.6	43				
15	6645	798	12.0	-13.0	16				
16	7000	788				240 / 20			
17	7130	784	12.0	-22.0	8				
18	8000	759				245 / 21			
19	9000	732				250 / 20			
20	10019	705	7.6	-31.4	4	255 / 18	LGT		
21	10211	700	7.2	-26.8	7	245 / 22			
22	10676	688	6.2	-18.8	15				

Summary Listing		Complete Listing		Interval Listing		Data Analyses		Severe Weather	
Level	Height (ft-MSL)	Pres (mb)	T (C)	Td (C)	RH (%)	DD / FF (deg / kts)	CAT (FAA)	LLWS	Icing - (AFGWC)
1	591	994	15.6	12.4	81	170 / 5			
2	789	987	17.2	12.2	72				
3	932	982	19.8	12.8	64				
4	1077	977	20.2	12.2	60		XTR	LIGHT	
5	2080	943	19.6	10.6	56	230 / 32			
6	2623	925	18.0	10.0	59	230 / 31			
7	3000	913				230 / 31			
8	4000	880				225 / 31			
9	4237	873	13.4	8.6	73				
10	4332	870	13.8	5.8	58				
11	4396	868	15.0	-1.0	33				
12	4458	866	16.8	m					
13	4582	862	17.2	m			MDT		
14	4958	850	17.0	m		230 / 23	LGT		
15	6000	817				225 / 20	MDT		
16	7000	787				205 / 18			
17	7853	762	13.0	m					
18	8000	758				210 / 17			
19	9000	729				205 / 15			
20	10059	700	8.0	m		205 / 14	LGT		
21	11000	675				180 / 12			
22	12000	649				190 / 10			