


Power Chart, Lycoming O-360-A



Power Setting Table — Lycoming Model O-540-A1A5, 250 HP Engine

Press. Alt. 1000 Feet	Std. Alt. Temp. °F	138 HP — 55% Rated Approx. Fuel 10.3 Gal./Hr. RPM AND MAN. PRESS.				163 HP — 65% Rated Approx. Fuel 12.3 Gal./Hr. RPM AND MAN. PRESS.				188 HP — 75% Rated Approx. Fuel 14.0 Gal./Hr. RPM AND MAN. PRESS.		
		2100	2200	2300	2400	2100	2200	2300	2400	2200	2300	2400
SL	59	21.6	20.8	20.2	19.6	24.2	23.3	22.6	22.0	25.8	25.1	24.3
1	55	21.4	20.6	20.0	19.3	23.9	23.0	22.4	21.8	25.5	24.8	24.1
2	52	21.1	20.4	19.7	19.1	23.7	22.8	22.2	21.5	25.3	24.6	23.8
3	48	20.9	20.1	19.5	18.9	23.4	22.5	21.9	21.3	25.0	24.3	23.6
4	45	20.6	19.9	19.3	18.7	23.1	22.3	21.7	21.0	24.8	24.1	23.3
5	41	20.4	19.7	19.1	18.5	22.9	22.0	21.4	20.8	—	23.8	23.0
6	38	20.1	19.5	18.9	18.3	22.6	21.8	21.2	20.6	—	—	22.8
7	34	19.9	19.2	18.6	18.0	22.3	21.5	21.0	20.4	—	—	—
8	27	19.4	18.8	18.2	17.6	—	21.3	20.7	20.1	—	—	—
9	31	19.6	19.0	18.4	17.8	—	—	20.5	19.9	—	—	—
10	23	19.1	18.6	18.0	17.4	—	—	—	19.6	—	—	—
11	19	18.9	18.3	17.8	17.2	—	—	—	—	—	—	—
12	16	18.6	18.1	17.5	17.0	—	—	—	—	—	—	—
13	12	—	17.9	17.3	16.8	—	—	—	—	—	—	—
14	9	—	—	17.1	16.5	—	—	—	—	—	—	—
15	5	—	—	—	16.3	—	—	—	—	—	—	—

To maintain constant power, correct manifold pressure approximately 0.17" Hg for each 10° F. variation in carburetor air temperature from standard altitude temperature. Add manifold pressure for air temperatures above standard; subtract for temperatures below standard.